



CRYSTAL-POX

Crystal Epoxy Resin for Stone.

AVAILABLE OPTIONS: ▼

COLOUR ▶ Crystal
 UNITS ▶ 25 Kg
 1000 Kg



ref. 092404

USE: ▼



Special for Floors



It needs to be mixed with a 4:1 ratio of A component with B component, to achieve a perfect hardening



Use for inside and outside



Material of liquid consistency

MORE INFORMATION ▼



VISIT our channel
 YouTube

AbrasivosAlicante



ANY DOUBT?

CALL US

(+34) 965 112 713

PROPERTIES: ▼

Epoxy Systems specially formulated for the reinforcement with fiberglass and filtering of Marbles and Granites. Our systems provide an extraordinary mechanical resistance to temperature, fire, moisture and corrosion by acids and bases. They also have great adhesive power, a minimum curing contraction and are differentiated by being extremely colourless.

Ecological. This product does not contain substances prohibited according to the regulation (CE) n°1907 / 2006



All our containers are **certified** by Ecoembes Recycling Company.



Product destined to **professional use.**



SPECIAL FILTERING



R350 + B350



Time required for the adhesive, mastic or resin to change viscosity and begin curing, once mixed with the secant.



Low viscosity.



Extra liquid.



Extra crystal.



UV protect



R450 + B450



Time required for the adhesive, mastic or resin to change viscosity and begin curing, once mixed with the secant.



Low viscosity.



Extra liquid.



Extra crystal.



UV protect



SPECIAL REINFORCEMENT



R1000+B1000



Time required for the adhesive, mastic or resin to change viscosity and begin curing, once mixed with the secant.



Low viscosity.



Extra liquid.



Extra crystal.



Low viscosity.



R450 + B450



Time required for the adhesive, mastic or resin to change viscosity and begin curing, once mixed with the secant.



Low viscosity.



ISO 9001:2015 CERTIFIED
 www.abrasivosalicante.com

ABRASIVOS
ALICANTE